

**20/300LFN Ec £890**

20 Litre Capacity

Chamber Dimensions WxDxH: 240 x 280 x 340mm

External Dimensions WxDxH: 460 x 680 x 640mm

1KW Power Rating, Single Phase, 13A UK Plug

Fan (constant speed), 2 shelves (5 positions)

**60/300LFN - £1,270**

60 Litre Capacity

Chamber Dimensions WxDxH: 380 x 380 x 420mm

External Dimensions WxDxH: 600 x 760 x 720mm

2KW Power Rating, Single Phase, 13A UK Plug

Fan with controller (1-10 speeds or off)

End of program buzzer, 3 shelves (7 positions)

**120/300LFN - £1,540**

120 Litre Capacity

Chamber Dimensions WxDxH: 550 x 400 x 580mm

External Dimensions WxDxH: 750 x 780 x 880mm

2.2KW Power Rating, Single Phase, 13A UK Plug

Fan with controller (1-10 speeds or off)

End of program buzzer, 3 shelves (7 positions)

**220/300LFN - £2,020**

220 Litre Capacity

Chamber Dimensions WxDxH: 730 x 500 x 620mm

External Dimensions WxDxH: 930 x 880 x 915mm

4KW Power Rating, Single Phase, fitted with IEC

60309 P+N+E (Blue Industrial Circular) Plug,

Fan with controller (1-10 speeds or off)

End of program buzzer, 3 shelves (7 positions)

**Controller features***Self-tuning - Ramp Dwell Program - Trending with**240 data points for up to 5 days of trending**(samples interval of 1sec to 30min) - 180 x 60**pixel graphic/real text LCD screen (67 x 37mm) -**On screen navigation help - 0.1° or 1° resolution**(0.1°C by default)***SNOL 20, 60, 120 & 220  
/300LFN Ovens**

The new SNOL 20, 60, 120, & 240 /300LFN electric laboratory ovens are designed for low temperature thermal treatment such as drying, heating and thermal testing in an air-flow assisted environment. Forced convection by the fan situated in back the panel provides more effective drying and quicker heating, as well as improved temperature uniformity throughout the chamber. With a temperature range of 50 to 300°C, the precision temperature control system provides good stability and uniformity for high quality results.



SNOL 20/300LFN Ec



SNOL 220/300LFN

*Microprocessor temperature controller**Built-in over-temperature protection system**Solid State Relay (SSR) control for longer life**High quality thermal insulation for increased energy efficiency**Heating from all four sides**Stainless steel chamber lining as standard**Hermetic door seal**Horizontal air flow**Control knob for internal or external air circulation selection**Short heating time**Low power consumption**Excellent chamber uniformity**1 year warranty on ovens**2 years warranty on instrument**Optional UKAS calibration & thermal surveys available at extra cost**Full UK spares & service available*

**TMS Europe Ltd**  
Unit 10 Stretfield Mill  
Bradwell, Hope Valley S33 9JT  
Tel: 01433 620535 Fax: 621492  
sales@tmseurope.co.uk  
www.tmseurope.co.uk